



超声清洗换能器

命名规则：

DC - 38 15 8 SH

德瓷代号

晶片外径

端面形状：
AH-直柱形
SH喇叭形

粉料类别：
4-P4
5-P5
8-P8

换能器频率 (KHz)

超声波清洗是利用超声波在清洗液中传播时的空化、辐射压、声流等物理效应，对清洗件上的污物产生的机械起剥落作用，同时能促进清洗液与污物发生化学反应，达到清洗物件的目的。



型号	谐振频率 /KHz	静态电容 /pF	谐振阻抗 /Ω	功率 /W	尺寸	
					发声面直径 /mm	高度/mm
DC-5020-4SH	20 ± 0.5	9000 ± 10%	≤25	120	68	46
DC-5028-8SH	28 ± 0.5	7000 ± 10%	≤25	120	68	66
DC-4528-4SH	28 ± 0.5	7800 ± 10%	≤25	100	68	66
DC-4528-8SH	28 ± 0.5	5000 ± 10%	≤25	100	68	66
DC-4540-4SH	40 ± 0.5	7800 ± 10%	≤25	100	52	48
DC-4520-8SH	20 ± 0.5	5000 ± 10%	≤25	100	68	94
DC-4528-8SH	28 ± 0.5	7800 ± 10%	≤25	100	68	66
DC-3825-4SH	25 ± 0.5	4800 ± 10%	≤25	60	59	80
DC-3828-4SH	28 ± 0.5	4800 ± 10%	≤25	60	59	68
DC-3880-4SH	80 ± 0.5	4800 ± 10%	≤25	60	40	60
DC-38120-4SH	28 ± 0.5	4800 ± 10%	≤25	60	59	68
DC-38135-4SH	28 ± 0.5	4800 ± 10%	≤25	60	59	68
DC-3840-4SH	40 ± 0.5	4800 ± 10%	≤25	60	45	50
DC-3828-8SH	28 ± 0.5	3500 ± 10%	≤25	60	59	68
DC-3840-8SH	40 ± 0.5	3500 ± 10%	≤25	60	45	50
DC-3528-4AH	28 ± 0.5	4000 ± 10%	≤25	50	45	82
DC-3540-4SH	40 ± 0.5	4000 ± 10%	≤25	50	45	55
DC-5430-4 AH	54 ± 0.5	3200 ± 10%	≤25	35	38	36