



压电陶瓷促动器

方 形	电压	产品尺寸	电容	位移	最大推力/拉力
DCSA3-R12H50	150V	Ø12 x 47 mm	3.0 μF $\pm$ 15%	43.0 μm $\pm$ 15%	800/100 N
DCSA3-R12H80	150V	Ø12 x 81 mm	4.5 μF $\pm$ 15%	57.0 μm $\pm$ 15%	800/100 N
DCSA3-R12H100	150V	Ø12 x 100 mm	6.0 μF $\pm$ 15%	80.0 μm $\pm$ 15%	800/100 N
DCSA3-R15H60	150V	Ø15 x 62 mm	6.0 μF $\pm$ 15%	36.0 μm $\pm$ 15%	1800/200 N
DCSA3-R15H80	150V	Ø15 x 81 mm	9.0 μF $\pm$ 15%	57.0 μm $\pm$ 15%	1800/200 N
DCSA3-R15H100	150V	Ø15 x 100 mm	12.0 μF $\pm$ 15%	80.0 μm $\pm$ 15%	1800/200 N
DCSA3-R15H140	150V	Ø15 x 134 mm	18.0 μF $\pm$ 15%	114.0 μm $\pm$ 15%	1800/200 N
DCSA3-R15H170	150V	Ø15 x 168 mm	24.0 μF $\pm$ 15%	152.0 μm $\pm$ 15%	1800/200 N
DCSA3-R15H200	150V	Ø15 x 195 mm	30.0 μF $\pm$ 15%	190.0 μm $\pm$ 15%	1800/200 N

配件信息:

壳体: 304不锈钢;

移动端: 钨钢半球端面、平面端面、内螺纹、外螺纹端面等;

底座: 内螺纹、外螺纹;

引线: 单芯同轴屏蔽线、双芯线;

引脚: 底座出线、侧面出线、密封式引脚;

连接器: LAMO标准连接器;

产品接受定制, 定制内容包括产品内部陶瓷及所用配件

